



We stock and sell a wide variety of quality fasteners for the tools in your market area. The information on this page is intended to help you in choosing the right fastener for your needs, or to simply serve as a handy reference guide to nails.

Ask your Mid-Atlantic Fasteners, LLC sales representative for a comprehensive list of fasteners, complete with item codes, sizes and the tools they fit!



**Clipped Head Strip, 28° Wire Collated**  
2" x .113 to 3/2" x .131



**Clipped Head Strip, 31° Paper Collated**  
2" x .113 to 3/2" x .131



**Round Head Strip, 21° FRH Plastic Collated**  
2" x .113 to 3/4" x .131



**Round Head Strip, 21° Joist Hanger/Plastic Collated**  
1 1/2" x .131 to 2 1/2" x .162



**Round Head Strip, 31° Joist Hanger/Paper Collated**  
1 1/2" x .131 to 2 1/2" x .162



**Round Head Coil, 15° Joist Hanger/Plastic Collated**  
1 1/2" x .131 to 2 1/2" x .148



**Round Head Coil, 15° Plastic Collated**  
1 1/4" x .083 to 2" x .090



**Round Head Coil, 15° Plastic Sheet Collated**  
2" x .092 to 2 1/2" x .092



**Round Head Coil, 0° Plastic Sheet Collated**  
2" x .097 to 2 3/4" x .097




**Round Head Wire Collated, 15° Flat Coil**  
1 1/4" x .099 to 3/4" x .131



**Round Head Wire Collated, Mini 15° Flat Coil**  
1 1/4" x .083 to 2" x .090



**Round Head Wire Collated, 15° Cone Coil**  
1 1/4" x .083 to 2" x .083



**Wire Collated, Galvanized Roofing**  
3/4" x .121 to 1 3/4" x .121



**Brads, 16 or 18 Gauge**  
1" to 2 1/2" x 16 ga.; 1/2" to 2" x 18 ga.



**Brads, Angled 15 Gauge Finish, Tape Collation**  
1" to 2 1/2" x 15 ga.




**Brads, Angled 15 Gauge Finish, Glue Collation**  
1 1/4" to 2 1/2" x 15 ga.



## 31° RoundDrive Strip Nails

- PRD06D113-HDGR-P**  
2" x .113 HDG Plus Rounddrive, 2000/box
- PRD08D113-HDG-PG**  
2 3/8" x .113 HDG Plus Rounddrive, 2000/box
- PRD08D113-HDGR-P**  
2 3/8" x .113 HDG Plus Rounddrive, 2000/box
- PRD10D113-HDG-PG**  
3" x .131 HDG Plus Rounddrive, 2000/box



## 15° Full Round Head Coil Nails

Wood to Steel

- PWCF05D080-S15CP**  
1 1/4" x .080 FRH Coil Nail, 16000/box
- PWCF08D099-SBC**  
2 1/2" x .099 FRH Coil Nail, 8250/box
- PWCF16D131-B-S**  
3 1/2" x .131 FRH Coil Nail, 4500/box



## Nail Terminology

- **Finishes:** Almost all nails are "bright"; which have a natural, uncoated steel finish. A variety of special finishes are also available.
- **Electro-Galvanized:** An electronic process which coats nails with a smooth, thin layer of rust-inhibiting zinc. Not recommended for ACQ applications.
- **Hot Dipped Galvanized:** Hot tumbling process which coats the nail with a heavy layer of zinc to provide excellent corrosion resistance.
- **Hardened:** A heat treating process which hardens steel nails.
- **Vinyl Coated:** This coating eases nail driving and provides greater holding power. Commonly used in pneumatic nailers.
- **Screw/Ring Shank:** Recommended where higher desire of holding power is required. Ring nails engage the wood fibers to enhance holding power.
- **Stainless Steel:** Recommended for use with pressure-treated lumber, such as ACQ (Alkaline Copper Quaternary). Pressure-treated lumber is extremely corrosive to any form of metal that comes in contact with it. Fastener failures caused by accelerated corrosion in applications where pressure-treated lumber is used could have significant consequences that can be avoided by using stainless steel.

### Wire Size

GAUGE	INCHES
15 gauge	.072"
14 gauge	.080"
13 gauge	.090"
12 1/2 gauge	.099"
12 gauge	.105"
11 1/2 gauge	.113"
11 gauge	.120"
10 1/2 gauge	.128"
10 gauge	.135"
9 1/2 gauge	.142"
9 gauge	.148"
8 gauge	.162"
7 gauge	.177"
6 gauge	.192"
4 gauge	.225"
2 gauge	.263"

### Penny Size

PENNY	INCHES
2D	1"
3D	1 1/4"
4D	1 1/2"
5D	1 3/4"
6D	2"
7D	2 1/4"
8D	2 1/2"
10D	3"
12D	3 1/4"
16D	3 1/2"
20D	4"
30D	4 1/2"
40D	5"
50D	5 1/2"
60D	6"

## Bulk Nails

### Bulk Nails, 50 lb. box

many different sizes and types available

#### DUPLIX NAILS

1 3/4" to 3 1/4"

#### HOT DIP BOX NAILS

2" to 3 1/2"

#### MASONRY NAILS

2" to 3"

#### PHOSPHOROUS COATED NAILS

1 3/8" to 1 1/2"

#### ROOF NAILS

2" to 3 1/2"

#### SINKER NAILS

2 3/8" to 3 1/4"

**SPECIFICATION**

where: L : Length  
S : Length of point  
D : Head diameter  
d : Shank diameter

**HOW TO DETERMINE DIMENSIONS OF NAIL**

**HEADS**

**SHANK**

**POINTS**



## Narrow Crown Staples 18 Gauge Galvanized



### 1800 "European 90 Series":

¼" to 1½" Leg, ¼" Crown


### SX:

⅝" to 1⅜" Leg, ⅞" Crown

### GSN:

⅝" to 1½" Leg, ⅜" Crown

## Medium Crown Staples 15, 16 or 18 Gauge Galvanized



### GS:

1" to 2" Leg, ½" Crown

### 100:

1" to 2" Leg, ⅞" Crown

### 7600:

1" to 2" Leg, ⅞" Crown

### BCS:

1" to 2" Leg, ½" Crown

### N:

½" to 2" Leg, ⅞" Crown

### Q:

1½" to 2½" Leg, ⅞" Crown

## Wide Crown Staples 14 and 16 Gauge Galvanized



### BCS:

¾" to 2" Leg, 1" Crown

### 1700:

¾" to 2" Leg, 1" Crown

### GSW:

⅝" to 2" Leg, 1⅝" Crown

### P:

1" to 2" Leg, 1" Crown

## Fine Wire Staples



### C:

¼" to ⅝" Leg, ⅜" Crown

### F:

¼" to ½" Leg, ½" Crown

### 3000:

¼" Leg, ½" Crown

### B:

½" Leg, ½" Crown, 22 Ga.

### G:

½" to ⅝" Leg, ⅜" Crown, 20 Ga.

### SHCR:

⅝" Leg, ⅜" Crown

### STCR:

¼" to ⅞" Leg, ⅜" Crown

### 5000 (Chisel Point Leg):

¼" to ⅞" Leg, ½" Crown

### 7500 (Chisel Point Leg):

⅝" to ⅞" Leg, ⅞" Crown

## Corrugated Fasteners



### 416:

¼" Leg, 1" Crown

### 616:

⅝" Leg, 1" Crown

### 816:

½" Leg, 1" Crown

### GC20:

⅝" and ½" Leg, 1" Crown

## We Stock & Sell More Than Just The Fasteners Shown In This Catalog

We stock and sell a wide variety of quality fasteners for the tools in your market area. The information on this page is intended to help you in choosing the right fastener for your needs, or to simply serve as a handy reference guide to staples. For a comprehensive list of fasteners, complete with item codes, sizes and the tools they fit, ask your Mid-Atlantic Fasteners, LLC sales representative for more information!

A19/A11



### 5400:

⅝" to ⅞" Leg, ⅞" Crown

### A19:

¼" Leg, ⅜" Crown

### A11:

¼" to ⅞" Leg, ⅜" Crown

5400



## Collated Screws



### FEATURES

- Collated screws are available in a variety of sizes for all ranges of screw drivers and screwguns
- Collated screws make even the novice or apprentice user as fast and efficient as the most experienced bulk screw user
- Eliminates waste experienced with bulk screws (typically 10-15%)

## OUR MOST POPULAR COLLATED SCREWS

<b>DWC114PS</b>	#6 x 1 1/4" Coarse Drywall Screw
<b>DWC158PS</b>	#6 x 1 1/2" Coarse Drywall Screw
<b>DWF114PS</b>	#6 x 1 1/4" Fine Thread Drywall - Steel
<b>DWF158PS</b>	#6 x 1 1/2" Fine Thread Drywall - Steel
<b>WSNTL134S</b>	#8 x 1 3/4" Zinc Subfloor Screw
<b>WSNTL212S</b>	#8 x 2 1/2" Zinc Subfloor Screw
<b>WSNTL2LS</b>	#8 x 2" Zinc Subfloor Screw
<b>WSNTLG212S</b>	#8 x 2 1/2" Galvanized Deck Screw
<b>WSNTLG3S</b>	#8 x 3" Galvanized Deck Screw
<b>DCLG212S</b>	#9 x 2 1/2" Square Drive Gray Composi-Lok Deck Screw
<b>DCLG3S</b>	#9 x 3" Square Drive Gray Composi-Lok Deck Screw
<b>DCLT212S</b>	#9 x 2 1/2" Square Drive Tan Composi-Lok Deck Screw
<b>DCLT3S</b>	#9 x 3" Square Drive Tan Composi-Lok Deck Screw
<b>DCLR212S</b>	#9 x 2 1/2" Square Drive Red Composi-Lok Deck Screw
<b>DCLR3S</b>	#9 x 3" Square Drive Red Composi-Lok Deck Screw
<b>DCLB212S</b>	#9 x 2 1/2" Square Drive Brown Composi-Lok Deck Screw
<b>DCLB3S</b>	#9 x 3" Square Drive Brown Composi-Lok Deck Screw
<b>PPSD11516S</b>	#8 x 1 15/16" Wood to Steel Screw
<b>CB3BLG112S</b>	#10 x 1 1/2" Cement Backerboard Screw
<b>PHSD34S</b>	#8 x 3/4" Pan Head Screw

## Bulk Screws



Bulk screws are available in a variety of sizes for all ranges of screw drivers

### SOME OF THE STYLES WE CARRY

- Bugle Screws
- Bugle Course Screws
- Cement Screws
- Hex Washer Screws
- Drywall Screws
- Self-Drilling Screws
- Hex Head Wood Screws

## Bolts, Nuts and Washers

Bolts, nuts and washers are available in a variety of sizes for all your application needs

### SOME OF THE STYLES WE CARRY

- All-Thread Rod, Zinc
- Carriage Bolt, Zinc
- Lag Screw
- Hex Bolt
- Hex Nut, Finished
- USS Flat Washer
- Fender Washer

### A Note On ACQ (Alkaline Copper Quaternary) and Fastener Recommendations when using Pressure Treated Lumber

On January 1, 2004, government mandates went into effect requiring companies engaged in pressure-treating lumber as a form of preservative to cease using chemical compounds that contain arsenic. Chromated Copper Arsenic, or CCA, was the most common compound used in the market and its use will nearly cease as a result.

In response to this mandate, several formulations have been hitting the market. While they all will conform to the new government standards for toxicity, almost all of them will be extremely corrosive to any form of metal that comes in contact with wood preserved with them. This includes fasteners, framing hardware, strapping and any other metallic objects.

Until more is understood about the effects of the various formulations on the market with metallic objects in general and fasteners in particular, we recommend the use of stainless steel as the basis material for fasteners used in pressure-treated lumber. The peace of mind afforded by using stainless steel far outweighs the cost in what is currently an uncertain situation. Fastener failures caused by accelerated corrosion in the applications where preserved lumber is used could have significant consequences that can be avoided by using stainless steel.

Please refer to the fastener manufacturer's web site for their application recommendations. Your Mid-Atlantic Fasteners' sales team will also be happy to help you with fastener recommendations to meet your application requirements.