



FC1500HBP2 "The Baby Bull" Electric Direct Drive



FEATURES

- Motor features: 1.5 HP, 3400 RPM, low amp draw, overload protected with manual reset, 115 volt
- Performance: 7.6 cu. ft. displaced, 3.6 cu. ft. free air at 100 PSI
- Pump features: Rol-Air quality, single stage, ball bearings, cast-iron cylinder, stainless steel reed valves and splash lubrication ensure longer pump life
- 13" long x 12" wide x 20" high; weighs 33 lbs.
- Tank capacity: 1.5 gallons

Item No. FC1500HBP2

FC1500HS3 "The Baby Bull" Electric Direct Drive



FEATURES

- Motor features: 1.5 HP, 3400 RPM, low amp draw, overload protected with manual reset, 115 volt
- Performance: 7.6 cu. ft. displaced, 3.6 cu. ft. free air at 100 PSI
- Pump features: Rol-Air quality, single stage, cast-iron cylinder, stainless steel reed valves and splash lubrication ensure longer pump life
- 20" long x 9" wide x 18" high; weighs 38 lbs.
- Tank capacity: 2.5 gallons

Item No. FC1500HS3

FC2002 "The Bull" Electric Direct Drive



FEATURES

- Motor features: 2 HP, 3400 RPM, low amp draw, overload protection with manual reset, 115 volt
- Performance: 7.8 cu. ft. displaced, 4.0 cu. ft. free air @ 100 PSI
- Pump features: Rol-Air quality, single stage, ball bearings, cast-iron cylinder, stainless steel reed valves and splash lubrication ensure longer pump life
- 20" long x 15" wide x 17" high; weighs 64 lbs.
- Tank capacity: 4.3 gallons

Item No. FC2002

FC2002HBP6 "The Bull" Electric Direct Drive



FEATURES

- Motor features: 2 HP, 3400 RPM, low amp draw, overload protection with manual reset, 115 volt
- Performance: 7.6 cu. ft. displaced, 4.0 cu. ft. free air at 100 PSI
- Pump features: Rol-Air quality, single stage, cast-iron cylinder, stainless steel reed valves and splash lubrication ensure longer pump life
- 16" long x 14" wide x 31" high; weighs 70 lbs.
- Tank capacity: 5.3 gallons

Item No. FC2002HBP6

D2000HBP6 Electric Direct Drive



FEATURES

- Motor features: 2 HP, 3400 RPM, low amp draw, overload protection with manual reset, 115 volt,
- Performance: 7.8 cu. ft. displaced, 4.3 cu. ft. free air at 100 PSI
- Pump features: heavy-duty, single stage, ball bearings, intake filter/silencer, stainless steel reed valves and splash lubrication ensure long pump life
- 16" long x 14" wide x 31" high; weighs 70 lbs.
- Tank capacity: 5.3 gallons

Item No. D2000HBP6

D2002HPV5 Electric Direct Drive



FEATURES

- Motor features: 2 HP, 3400 RPM low amp draw, overload protection with manual reset, 115 volt
- Performance: 7.8 cu. ft. displaced, 4.0 cu. ft. free air at 100 PSI
- Pump features: heavy-duty with cast iron cylinders, metal intake filter/silencer, stainless steel reed valves and splash lubrication ensure long pump life
- 18" long x 16" wide x 17" high; weighs 62 lbs.
- Tank capacity: 4.5 gallons

Item No. D2002HPV5

GD4000PV5H Gas Direct Drive

FEATURES

- Motor features: 4 HP Honda engine, cast-iron cylinder sleeve, overhead valves, on/off switch, dual element air cleaner, electronic ignition, low oil control
- Performance: 5.1 cu. ft. free air at 40 PSI, 4.4 cu. ft. free air at 100 PSI, 4.0 cu. ft. free air at 125 PSI
- Pump features: heavy-duty, single stage, splash lubricated, metal filter w/silencer, fan cooled and fixed rotation speed
- 22" long x 16" wide x 16" high; weighs 72 lbs.
- Tank capacity: 4.5 gallons



Item No. GD4000PV5H

5715K17 Electric Belt Drive

FEATURES

- Motor features: 1½ HP, 1725 RPM, open drip proof, 115/230 volt, overload protection with manual reset
- Performance: 10.1 cu. ft. displaced, 6.9 cu. ft. free air at 100 PSI
- Pump features: twin cast iron cylinders, hardened steel valve plates with swedish lamellar reed valves, aluminum alloy connecting rods with automotive-style inserts, and oil sight glass
- 46" long x 19" wide x 28" high; weighs 180 lbs.
- Tank capacity: 9 gallons



Item No. 5715K17

4090HK17-RG Gas Belt Drive

FEATURES

- Motor features: 5.5 HP Honda 4 cycle engine, complete die cast aluminum alloy with cast-iron sleeve, overhead valves, retractable starter, splash lubricated, low oil shutdown
- Performance: 13.1 cu. ft. displaced, 8.9 cu. ft. free air at 100 PSI
- Pump features: heavy-duty single stage, cast-iron twin cylinders, splash lubricated, cast-iron valve plates, oil sight gauge
- 46" long x 19" wide x 28" high; weighs 175 lbs.
- Tank capacity: 9 gallons



Item No. 4090HK17-FRG

6590HK18-RG Gas Belt Drive

FEATURES

- Motor features: 6.5 HP Honda 4 cycle engine, complete die cast aluminum alloy with cast-iron sleeve, overhead valves, retractable starter, splash lubricated, low oil shutdown
- Performance: 17.4 cu. ft. displaced, 13.1 cu. ft. free air at 100 PSI
- Pump features: heavy-duty, single stage, cast-iron twin cylinders, splash lubricated, cast-iron valve plates, oil sight gauge
- 46" long x 19" wide x 29" high; weighs 180 lbs.
- Tank capacity: 9 gallons



Item No. 6590HK18-FRG

V5160K25X Stationary Compressor

FEATURES

- Motor features: 5 HP motor, 3450 RPM, open drip-proof, 1 phase, 230 volt, overload protected
- Performance: 14.5 cu. ft. displaced, 10.6 cu. ft. free air at 175 PSI
- Pump features: heavy-duty, two stage, twin cylinders, multiple V-belt drive, low operating RPM's
- 30" long x 20" wide x 73" high; weighs 375 lbs.
- Tank capacity: 60 gallons
- Also available with 80 gallon tank



Item No. V5160K25X

8422HK30-RG Gas Belt Drive

FEATURES

- Motor features: 8 HP Honda 4 cycle engine, complete aluminum alloy with cast-iron sleeve, overhead valves, retractable starter, splash lubricated, low oil shutdown
- Performance: 24.4 cu. ft. displaced, 19.2 cu. ft. free air at 100 PSI
- Pump features: two stage pump, cast-iron cylinders, splash lubricated, cast-iron valve plates, oil sight gauge
- 46" long x 28" wide x 35" high; weighs 285 lbs.
- Tank capacity: 9 gallons



Item No. 8422HK30-FRG