

Machine Grade Stretch Film and Netting

Has your company looked at right gauge recently?

Let your Carlson Systems Account Manager show you how to stretch your packaging dollars by utilizing the right gauge for your application!



Machine Grade Stretch Film

Cast Machine Film

Quiet, clear, high performance, excellent puncture. Good for A, B and C type loads, with good cling. Consult your Account Manager for the recommended maximum stretch for each type of film.

Two-Sided Cling

| FILM WIDTH | GAUGE | FEET/ROLL |
|------------|-------|-----------|
| 20" | 50 | 9000' |
| 20" | 60 | 7500' |
| 30" | 60 | 7500' |
| 20" | 70 | 6500' |
| 30" | 70 | 6500' |
| 10" | 80 | 6000' |
| 20" | 80 | 6000' |
| 30" | 80 | 6000' |
| 20" | 90 | 5000' |
| 30" | 90 | 5000' |
| 20" | 100 | 4500' |
| 20" | 115 | 3750' |
| 30" | 115 | 3750' |

One-Sided Cling

| FILM WIDTH | GAUGE | FEET/ROLL |
|------------|-------|-----------|
| 20" | 50 | 9000' |
| 20" | 60 | 7500' |
| 30" | 60 | 7500' |
| 20" | 70 | 6500' |
| 30" | 70 | 6500' |
| 10" | 80 | 6000' |
| 20" | 80 | 6000' |
| 30" | 80 | 6000' |
| 20" | 90 | 5000' |
| 30" | 90 | 5000' |
| 20" | 100 | 4500' |
| 20" | 115 | 3750' |
| 30" | 115 | 3750' |

One-Sided Cling (Metric)

| FILM WIDTH | GAUGE | FEET/ROLL |
|------------|-------|-----------|
| 19.7" | 55 | 8725' |
| 19.7" | 65 | 7385' |
| 19.7" | 70 | 6000' |
| 29.5" | 70 | 6000' |
| 19.7" | 75 | 6400' |
| 19.7" | 105 | 4250' |

One-Sided Cling (New Resin Technology)

Quiet, clear, excellent performance, excellent puncture. Excellent for A, B and C type loads, with excellent cling and very strong.

| FILM WIDTH | GAUGE | FEET/ROLL |
|------------|-------|-----------|
| 19.7" | 51 | 7500' |
| 20" | 51 | 9000' |
| 19.7" | 57 | 6500' |
| 19.7" | 63 | 6000' |
| 20" | 63 | 7250' |
| 29.5" | 63 | 6000' |
| 19.7" | 71 | 5500' |
| 19.7" | 79 | 5000' |
| 19.7" | 87 | 4500' |
| 29.5" | 87 | 4500' |
| 19.7" | 98 | 3750' |

Cast Film Properties

- Consistent cling
- Excellent clarity and gauge control
- Glow
- More resistance to tearing
- Excellent optics
- Quiet unwind
- Consistent film thickness

Blown Film Properties

- Tougher, greater puncture resistance
- High force on load; stiff
- Hazy and dull
- Excellent performance without pre-stretch and in cold temperatures
- Noisy unwind

Σ Sigma Stretch® Film

Blown Machine Film

Loud release, high performance, excellent puncture. Good for A, B and C type loads, with excellent cling. Consult your Account Manager for the recommended maximum stretch for each type of film.

Two-Sided Cling

| FILM WIDTH | GAUGE | FEET/ROLL |
|------------|-------|-----------|
| 20" | 70 | 6500' |
| 20" | 80 | 5000' |
| 20" | 80 | 6000' |
| 30" | 80 | 6000' |
| 20" | 90 | 5000' |
| 20" | 120 | 3750' |

Stretch Netting

Stretch netting secures pallet loads without stopping air flow, providing ventilation and keeping condensation from forming on loads. Perfect for the food industry.

Strong, disposable plastic netting is used for containment of small debris, especially during transporting. Call for more information.



Footage per roll varies by supplier. Ask your Carlson Systems Account Manager for more details.